

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
15 March 2001 (15.03.2001)

PCT

(10) International Publication Number  
**WO 01/18529 A1**

(51) International Patent Classification<sup>7</sup>: G01N 21/64,  
G01J 3/02, F16B 21/02, G01R 19/165, H01R 13/66

(21) International Application Number: PCT/AU00/01058

(22) International Filing Date:  
6 September 2000 (06.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PQ 2705 8 September 1999 (08.09.1999) AU

(71) Applicant (for all designated States except US): VARIAN  
AUSTRALIA PTY LTD [AU/AU]; 679 Springvale Road,  
Mulgrave, Victoria 3170 (AU).

Vanessa, Mary, Joy [AU/AU]; 22A Bembridge Avenue,  
Frankston, Victoria 3199 (AU). KASELIS, Martin  
[AU/AU]; 62 Reilly Street, Ringwood, Victoria 3134  
(AU). EGLI, Hans, Heinrich [AU/AU]; 4 Gumtree  
Grove, Belgrave Heights, Victoria 3160 (AU).

(74) Agent: PHILLIPS ORMONDE & FITZPATRICK; 367  
Collins Street, Melbourne, Victoria 3000 (AU).

(81) Designated States (national): AU, JP, US.


(84) Designated States (regional): European patent (DE, FR,  
GB, IT).

Published:  
— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventors; and  
(75) Inventors/Applicants (for US only): McCALLUM,

(54) Title: SPECTROMETER ATTACHMENTS AND PHOSPHORESCENCE DECAY MEASUREMENT



(57) Abstract: A spectrometry instrument, e.g., for time-resolved spectroscopy, has quick-change exchangeable accessories (48, 50, 52) which are manually attached via rotation of a camming means to engage and lock a stud member. A circuit element in each accessory (48, 50, 52), such as a resistor or a configured pin connection, acts to generate a voltage in the instrument that uniquely identifies which accessory is attached. A method for measuring a phosphorescence decay characteristic includes applying an excitation pulse to a sample (34); obtaining emission intensity data for a sequence of time delays following the excitation pulse; repeating for at least one further excitation pulse using a different sequence of time delays; and interleaving the data from different excitation pulses to construct a decay characteristic.

WO 01/18529 A1